

Dual Guard™ Extra Heavy Duty & Heavy Duty

(Any Fuel Gas & Oxygen)

Extra Heavy Duty DG900 Series Cuts Up To 24" (610mm)

Dual Guard™ hand cutting torches are built for the toughest jobs. They feature a built-in head flashback arrestor, reversible cutting lever and ease-on oxygen for smooth starts. The torch is also designed with a heavy wall manganese bronze head for durability and resistance to heat warping.

Heavy Duty 200 Series Cuts Up To 12" (305mm)

Dual Guard™ hand cutting torches are built for the toughest jobs. They feature a built-in head flashback arrestor, reversible cutting lever and ease-on oxygen for smooth starts. The torch is also designed with a heavy wall manganese bronze head for durability and resistance to heat warping. All Dual Guard™ torches listed below are covered by Smith's "Lifetime" warranty.

- 3 tube "in-tip" mix design keeps gases separated until reaching the tip
- Ergonomic reversible cutting lever, for top or bottom mounting
- Exceptional ease-on oxygen feature
- Uses long lasting "Soft Seat" Graf-Tite® cutting tips
- Replaceable hose connections
- Wide array of cutting, gouging and specialty tips available
- Versatile - for use with acetylene, propane, propylene, MAPP® and many other gases
- Superior "ease-on" cutting jet action reduces tip-clogging and slag blow-back in piercing operations

100% TESTED AND INSPECTED

Available Torch Head Angles

Heavy duty manganese bronze head. Choice of 75°, 90° and 180°.

Stock No.	Head Angle	Length inch/metric	See Pages 32 - 37 For Cutting Tips
DG920B	180°	21"/533mm	Oxygen/Acetylene: SC12-00 thru SC12-6 SC56-1 thru SC56-5
DG925B	75°	21"/533mm	
DG929B	90°	21"/533mm	Oxygen/Propane Oxygen/Propane Based: SC40-0 thru SC40-4 SC46-2 thru SC46-6
DG220	180°	21"/533mm	
DG225	75°	20-1/2"/521mm	SC50-0 thru SC50-6 Oxygen/Propylene: SC60-1, SC60-2 SC2-2, SC2-4
DG229	90°	20-1/2"/521mm	
<p>Part No. 16219 Extreme ease-on oxygen high pressure seat for metal washing available for DG900 Series Torches.</p>			

NOTE: May be used with all Heavy Duty Special Purpose Tips.

DG & SC Series Hand Torch Valve Assembly Replacement LW14B-1
(excluding SC700 Series Tuf-Tony™)



DG929B
Length
21"
(533mm)

Weight
3-1/2 lbs.
(1.54kg)



Torches



16229
Adjustable Circle
Cutting Guide
Cutting range from 5/8" - 12" holes



DG SERIES TORCHES INCLUDE
SINTERED METAL INLET FILTERS.



DG229
Length
20-1/2"
(521mm)

Weight
2 lbs. 14 oz.
(1.29kg)